

PRODUCT SPECIFICATIONS

DRYER MODEL	INLET FLOW		PRESSURE DROP PSI	VOLTAGE	IN/OUT CONNECTIONS	POWER CONSUMPTION KW	REFRIGERANT	HEIGHT		WIDTH		DEPTH		WEIGHT LBS
	NM ³ /H	SCFM						IN	MM	IN	MM	IN	MM	
CRPC75	127	75	2.9	115/1/60	1" NPT	0.54	R134A	30	751	15	381	24	603	120
CRPC100	170	100	3	115/1/60	1" NPT	0.62	R134A	28	711	15	381	31	781	147
CRPC150	255	150	1.7	115/1/60	1" NPT	1.04	R407C	30	751	18	443	36	911	203
			3.6	230/1/60	2" NPT	0.85		30	751	18	443	36	911	189
CRPC200	340	200	2.2	230/1/60	2" NPT	1.32	R407C	30	751	18	443	38	961	217
			2.1	460/3/60		1.26	R134A	30	751	18	443	38	961	244
CRPC300	509	300	3.6	460/3/60	2" NPT	1.99	R407C	36	911	20	494	44	1111	324
CRPC400	680	400	2.5	230/1/60	2" NPT	2.54	R407C	36	911	20	494	44	1111	335
CRPC450	765	450	3.0	460/3/60	2" NPT	3.23	R407C	41	1032	20	494	50	1253	366
CRPC550	935	550	3.0	460/3/60	2" NPT	3.42	R407C	41	1032	20	494	50	1253	396

Performance data presented in accordance with ISO 7183 (Option A2) conditions: 100°F inlet temperature, 100°F ambient temperature and 100 psig conditions.