

R-SERIES | 7.5-15 HP RECIPROCATING COMPRESSORS

Pump Model R-30D

Customized Solutions


Champion R-Series compressors provide the reliable, high quality compressed air that you've come to expect from Champion. R-Series compressors offer a wide selection of configurations and top-quality available options. With superior, professional-grade components and rugged standard features, R-Series compressors are guaranteed to provide the performance you demand.

Standard Features

- Loadless starting (via centrifugal unloader)
- ASME interstage pressure relief valve
- ODP NEMA 1760 RPM motor
- 10 Micron industrial grade intake air filter
- ASME coded receiver
- 0-300 PSIG air pressure gauge
- Available voltages
 - 1 Phase—115/208-230
 - 3 Phase—208/230/460/575
- 1-Year package warranty
- 5-Year pro-rated pump warranty

Available Options

- Multiple tank sizes and variations
- Electric or engine driven
- NEMA 4 full-voltage starter upgrade
- Premium efficiency motor upgrades
- Control panel upgrades
- Aftercooler with or without moisture separator
- Low oil-level monitor (NEMA 1 or 4)
- Dual control
- Vibration isolators
- High temperature switch (NEMA 1 or 4)
- Available switches (NEMA 1 or 4)
 - Test/Off/Auto, Hand/Off/Auto, Off/On
- Pneumatic or electric tank drain



BARE PUMP

MODEL	DIMENSIONS L x W x H INCHES	APPROX. SHIP WEIGHT LBS.	BORE DIA. INCHES	STROKE INCHES	# OF CYLINDERS	OIL CAPACITY QTS.	MIN/MAX PUMP RPM
R-30D	22.4 x 26 x 23.6	220	4.625 x 2.5	3	4	4	400/1050

BASE MOUNTED UNITS

MOTOR HP	R-SERIES CABRSA	DIMENSIONS L x W x H INCHES	APPROX. SHIP WEIGHT LBS.	125 PSI RATING		175 PSI RATING	
				RPM	CFM DEL'Y	RPM	CFM DEL'Y
7.5	BR7F	43 x 23 x 29	430	670	30	575	25.8
10	BR10	43 x 23 x 29	540	810	37.3	740	34.8
15	BR15F	43 x 23 x 29	550	1045	50.2	1045	49

SIMPLEX TANK MOUNTED UNITS

MOTOR HP	TANK CAPACITY GAL.	HORIZONTAL TANK MOUNTED			VERTICAL TANK MOUNTED			125 PSI RATING		175 PSI RATING	
		R-SERIES CASRSA	DIMENSIONS L x W x H INCHES	APPROX. SHIP WEIGHT LBS.	R-SERIES CASRSA	DIMENSIONS L x W x H INCHES	APPROX. SHIP WEIGHT LBS.	RPM	CFM DEL'Y	RPM	CFM DEL'Y
7.5	80	HR7-8	67 x 26 x 50	665	VR7-8	42.5 x 30 x 67	665	670	30	575	25.8
7.5	120	HR7-12	71 x 26 x 53	860	VR7-12	42.5 x 30 x 81	800	670	30	575	25.8
10	80	HR10-8	67.3 x 26 x 49.5	675	VR10-8	42.5 x 30 x 68.8	860	810	37.3	740	34.8
10	120	HR10-12	71.4 x 26 x 52.8	890	VR10-12	42.5 x 30 x 81	890	810	37.3	740	34.8
10	250	HR10-25	88.5 x 31 x 60	1295	N/A	N/A	N/A	N/A	N/A	N/A	N/A
15	80	HR15F-8	67.3 x 26 x 49.5	675	N/A	N/A	N/A	N/A	N/A	N/A	N/A
15	120	HR15F-12	71.4 x 26 x 52.8	840	VR15F-12	42.5 x 30 x 81	890	1035	50.2	1035	49
15	250	HR15F-25	88.5 x 31 x 60	1275	N/A	N/A	N/A	N/A	N/A	N/A	N/A

DUPLEX TANK MOUNTED UNITS

MOTOR HP	TANK CAPACITY GAL.	R-SERIES CADRSA	DIMENSIONS L x W x H INCHES	APPROX. SHIP WEIGHT LBS.	125 PSI RATING		175 PSI RATING	
					RPM	CFM DEL'Y	RPM	CFM DEL'Y
7.5 (2)	120	HR7D-12	83 x 30 x 56	1305	670	60	575	51.6
7.5 (2)	250	HR7D-25	88 x 33.1 x 61.3	1675	670	60	575	51.6
10 (2)	120	HR10D-12	83 x 30 x 56	1725	810	74.6	740	69.6
10 (2)	250	HR10D-25	88 x 33.1 x 61.3	2325	810	74.6	740	69.6
15 (2)	120	HR15DF-12	83 x 30 x 56	1860	1045	100.4	1045	98
15 (2)	250	HR15DF-25	88 x 33.1 x 61.3	2460	1045	100.4	1045	98

Simplex CFM values are doubled for duplex units. Duplex units have two motors and two pumps on one tank.

CHAMPION

1301 North Euclid Avenue
Princeton, Illinois 61356 USA
www.ChampionPneumatic.com/ContactUs.aspx
866-276-4330
www.ChampionPneumatic.com



©2015 Gardner Denver, Inc. Printed in U.S.A.
CR-R-R30 1st Ed. 11/15